

SPECIFICATIONS

Model	4 tiers	LGE-402(FB)			
	3 tiers	LGE-302(FB)			
	2 tiers	LGE-202(FB)			
	1 tier	LGE-102(FB)			
Rated Voltage		24V AC/DC (50/60Hz)			
Operating Voltage		Rated Voltage $\pm 10\%$			
Power Consumption		2.0W (LED) Per Unit 0.5W (Buzzer)			
Operating Temperature Range (Relative Humidity)		- 30°C to + 60°C (Less than 90%)			
Mounting	Location	Indoor Only			
	Direction	Upright Only			
Protection Rating		IP 54			
Vibration Resistance		44.1m / s ² (30Hz, Back and Forth:2h · Right to Left:2h · Up and Down:2h)			
Insulation Resistance		More than 1M Ω at 500VDC between the terminals and the chassis			
Withstanding Voltage		500VAC applied for 1min between terminals and chassis without breaking insulation			
Flashing Rate		60 ± 12 Flashes Per Minute			
Buzzer	Sound Level	85dB at 1m			
	Tone	Buzzer1: Fast Intermittent Buzzer2: Slow Intermittent			
Luminous Intensity	Red	Amber	Green	Blue	White
	1400mcd	2150mcd	1550mcd	400mcd	1200mcd
Mass (Tolerance $\pm 10\%$)	1 tier	2 tiers	3 tiers	4 tiers	-
	0.40kg	0.60kg	0.80kg	0.90kg	-
No.LGE-PDFE-EN					

- This product conforms to the CE requirements and shows the CE Marking.

PATLITE Corporation